

MOJO Jeep Grill Insert Instructions for JK/JL



Under the hood, there are six pins that will need to be pulled to install the insert. Same for JK and JL



Use a screwdriver to pry up the pins. Once lifted, they can be removed by hand or with a pair of pliers.



Once all six pins are removed, pull the grill slightly forward. (Figure 1) From the bottom of the grill, pull until the snap clips come out and release the grill. (Figure 2)



(Snap clips at bottom of grill)



(JL ONLY)

Lay your grill face down on cardboard box or towel so you don't scratch it. Remove the eight T-20 torx and phillips head screws from the back of the grill. See red marked spots on picture.



(JL ONLY)

Remove the four white snap clips on the back center of the factory grill insert. Remove the three white snap clips along the base of the grill. Press down on clips and slide out. See red marked spots on picture.



(JL ONLY)

Using a flathead screwdriver remove the four black clips along the bottom of the factory grill insert pieces.



(JL ONLY)

Remove center section of the factory grill insert and then remove both side sections of the factory insert.



Reinstall the grill onto the Jeep starting with the bottom snap clips first. Slide the insert in between the grill and the radiator. The insert will rest on the clips at the bottom interior of the grill itself. Reinstall the top push six pins.

NOTE: If your insert appears crooked once installed, please be sure the insert isn't resting on the sensor located on the bottom right of the grill. Shift slightly to correct. Push grill back into place, replace pins, and you're all set! No other tools or methods of attachment are necessary.

We hope you enjoy your purchase!

